



Hypermax ATV/UTV Belt Dimensional Information

Part #	O.C.	Top Width
UA400	33-5/32"	1-3/16"
UA401	37-5/16	1-7/16"
UA402	35-3/16"	11/16"
UA403	26-21/32"	11/16"
UA404	43-29/32"	1-3/16"
UA405	41-27/64"	31/32"
UA406	36-3/4"	1-29/64"
UA409	39-9/32"	1-1/4"
UA410	40-33/64"	1-9/32"
UA411	42-5/32"	1-3/64"
UA412	41"	1-5/32"
UA413	41"	1-5/32"
UA414	26-13/16"	45/64"
UA415	28-3/8"	11/16"
UA416	33-11/16"	1-11/64"
UA417	34-1/2"	1-13/64"
UA418	33-17/64"	1-1/8"
UA419	38-11/16"	1-5/16"
UA420	37-11/32"	1-19/64"
UA421	29-7/8"	23/32"
UA422	37"	1-19/64"
UA423	37-11/64	1-17/64"
UA424	41-7/32"	1-3/16"
UA425	36-61/64"	25/32"
UA426	40-57/64"	1-10/64"
UA427	43-37/64"	1-3/8"
UA428	42-15/64"	1-3/16"
UA429	43-47/64"	1-15/64"
UA433	52-1/8"	1-29/64"
UA434	43-15/64"	1-13/64"
UA435	37-7/64"	1-1/4"
UA436	35-3/16"	43/64"
UA437	37-5/16	1-7/16"
UA439	42-11/32"	1-1/4"
UA440	43-13/64"	1-3/8"
UA442	42-7/32"	1-17/64"
UA443	35-9/16"	1-5/16"
UA444	36-11/16"	15/16"
UA445	37-10/32"	1-7/16"
UA446	38-3/8"	1-5/16"
UA448	39-15/16"	1-1/4"

Please Note: The belt dimensions provided by Carlisle are for reference only. These dimensions should not be used to determine product functionality. Carlisle belts are built to exacting specifications and inspected with calibrated equipment at specified tensions to assure strict dimensional compliance. Belt dimensions can vary from one manufacturer to another based on proprietary design information.