

Ultimax Belt Dimensions

Please Note: The belt dimensions provided by Carlisle are for reference only.

These dimensions should not be used to determine product functionality.

Carlisle belts are built to exacting specifications and inspected with calibrated equipment at specified tensions to assure strict dimensional compliance.

Belt dimensions can vary from one manufacturer to another based on proprietary design information.

Max 2

Part #	O.C	TopWidth
MAX1032M2	43-5/32	1-15/32
MAX1034M2	42-27/32	1-5/32
MAX1035M2	48-29/32	1-13/32
MAX1039M2	44-21/32	1-5/32
MAX1042M2	43-29/32	1-5/32
MAX1048M2	43-1/32	1-13/32
MAX1049M2	42-31/32	1-7/32
MAX1060M2	43-9/32	1-5/32
MAX1062M2	43-13/32	1-13/32
MAX1065M2	42-9/32	1-9/32
MAX1067M2	45-15/32	1-13/32
MAX1071M2	44-13/32	1-7/32
MAX1078M2	46-15/32	1-7/32
MAX1080M2	45-31/32	1-7/32
MAX1082M2	43-9/32	1-7/32
MAX1084M2	43-25/32	1-7/32
MAX1089M2	42-17/32	1-7/32
MAX1092M2	42-1/2	1-5/32
MAX1093M2	45-9/32	1-7/32
MAX1103M2	43-25/32	1-9/32
MAX1104M2	47-21/32	1-7/32
MAX1105M2	47-1/32	1-13/32
MAX1106M2	43-3/32	1-7/32
MAX1107M2	46-29/32	1-7/32
MAX1108M2	43-29/32	1-13/32
MAX1109M2	46-7/32	1-13/32
MAX1110M2	41-13/64	59/64
MAX1112M2	45-13/32	1-13/32
MAX1114M2	42-9/32	1-7/32
MAX1115M2	43-13/32	1-5/32
MAX1116M2	44-11/32	1-5/32
MAX1117M2	43-15/32	1-7/32
MAX1118M2	44	1-23/64
MAX1119M2	45-1/64	1-13/32
MAX1122M2	44-29/32	1-7/32
MAX1123M2	45-13/32	1-7/32
MAX1130M2	47-17/32	1-13/32
MAX1131M2	48-25/32	1-13/32
MAX1132M2	47-17/32	1-3/8
MAX1133M2	41	1-5/32

Ultimax 3 Belt Dimensions

Please Note: The belt dimensions provided by Carlisle are for reference only.

These dimensions should not be used to determine product functionality.

Carlisle belts are built to exacting specifications and inspected with calibrated equipment at specified tensions to assure strict dimensional compliance.

Belt dimensions can vary from one manufacturer to another based on proprietary design information.

Part #	O.C	TopWidth
125-4320U3	43-15/64	1-15/64
125-4616U3	46-1/4	1-15/64
131-4400U3	44-9/32	1-5/16
138-4310U3	43-10/64	1-23/64
138-4316U3	43-7/16	1-23/64
138-4332U3	43-15/64	1-23/64
138-4340U3	43-13/16	1-3/8
138-4353U3	43	1-25/64
138-4400U3	44-13/64	1-3/8
138-4416U3	44-7/64	1-23/64
138-4432U3	44-1/2	1-23/64
138-4532U3	45-1/2	1-23/64
138-4548U3	45-59/64	1-3/8
138-4628U3	46-39/64	1-3/8
138-4716U3	47-27/64	1-3/8
138-4748U3	47-39/64	1-11/32
138-5120U3	51-9/32	1-25/64
138-5232U3	52-43/64	1-3/8
140-4352U3	43-13/16	1-7/16
140-4748U3	47-19/32	1-3/8
140-5157U3	52-1/16	1-25/64
144-4340U3	43-15/32	1-23/64
144-4353U3	44	1-13/32
144-4616U3	46-7/64	1-25/64
144-4640U3	46-15/32	1-13/32
144-4740U3	47-15/32	1-13/32
144-4824U3	48-7/32	1-13/32
144-4900U3	49-1/64	1-27/64
144-5018U3	50-3/8	1-27/64
144-5028U3	50-17/32	1-27/64
145-4358U3	43-29/32	1-3/8
146-4440U3	44-13/64	1-7/16
146-4540U3	45-13/64	1-7/16
146-4626U3	46-26/64	1-26/64
147-4407U3	48-11/32	1-29/64
147-4416U3	44-1/4	1-7/16
147-4457U3	44-57/64	1-29/64
147-4462U3	44-31/32	1-7/16
147-4524U3	45-3/8	1-29/64
147-4711U3	47-5/32	1-29/64

Ultimax XS Belt Dimensions

Please Note: The belt dimensions provided by Carlisle are for reference only.

These dimensions should not be used to determine product functionality.

Carlisle belts are built to exacting specifications and inspected with calibrated equipment at specified tensions to assure strict dimensional compliance.

Belt dimensions can vary from one manufacturer to another based on proprietary design information.

Part #	O.C	TopWidth
XS801	45-11/64	1-7/16
XS802	48-7/32	1-3/8
XS803	44-7/32	1-7/16
XS804	44-7/8	1-7/16
XS805	45-1/8	1-3/8
XS806	44-1/16	1-7/16
XS807	51-25/32	1-13/32
XS808	44-23/32	1-7/16
XS809	47-3/32	1-7/16
XS810	44-11/64	1-7/16
XS811	45-23/64	1-7/16
XS812	44-27/32	1-7/16
XS813	46-7/64	1-7/16
XS814	49-41/64	1-7/16
XS815	48-27/32	1-7/16
XS816	48-3/32	1-7/16
XS817	46-1/8	1-15/32
XS818	43-11/16	1-15/32

Ultimax ATV Belt Dimensions

Please Note: The belt dimensions provided by Carlisle are for reference only.

These dimensions should not be used to determine product functionality.

Carlisle belts are built to exacting specifications and inspected with calibrated equipment at specified tensions to assure strict dimensional compliance.

Belt dimensions can vary from one manufacturer to another based on proprietary design information.

Part #	O.C	TopWidth
UA400	33-5/32"	1-3/16"
UA401	36-27/32"	1-7/16"
UA402	35-3/16"	11/16"
UA403	26-21/32"	11/16"
UA404	43-29/32"	1-3/16"
UA405	41-27/64"	31/32"
UA406	36-3/4"	1-29/64"
UA407	33-15/32"	1-1/8"
UA409	39-9/32"	1-1/4"
UA410	40-33/64"	1-9/32"
UA411	42-5/32"	1-3/64"
UA412	41	1-5/32"
UA413	41	1-5/32"
UA414	26-13/16"	45/64"
UA415	28-3/8"	11/16"
UA416	33-11/16"	1-11/64"
UA417	34-1/2"	1-13/64"
UA418	33-17/64"	1-1/8"
UA419	38-11/16"	1-5/16"
UA420	37-11/32"	1-19/63"
UA421	29-7/8"	23/32"
UA422	37"	1-19/64"
UA423	37-11/64"	1-17/64"
UA424	41-7/32"	1-3/16"
UA425	36-61/64"	25/32"
UA426	40-57/64"	1-10/64"
UA427	43-37/64"	1-3/8"
UA428	42-15/64"	1-3/16"
UA429	43-47/64"	1-15/64"
UA433	52-1/8"	1-29/64"
UA434	43-15/64"	1-13/64"
UA435	37-7/64"	1-1/4"
UA436	35-3/16"	43/64"
UA437	37-5/16"	1-7/16"